

悬壁销 ▶ 螺钉固定型 法兰型

5日 发货
大批量 订购



①~⑥ 选择型式和参数按序号顺序进行订购。

型号 (① 代码) — ② 规格 — ③ Dg6 — ④ Y — ⑤ F — ⑥ M — ⑦ YC AD
 NRB FH — 6 — D6 — Y65 — F160 — M4 — YC



● 优惠价
 数量 1~9 10~
 价格 100% 另行报价
 未税价(元)

库存






CAD 2D 3D

代码	类型	材质		表面处理
		国标	相当	
NRBFH	螺钉固定型	45	S45C	发黑
NRBFJ				无电解镀锌
NRBFK		0Cr18Ni9	SUS304	—
NRBGH				发黑
NRBGJ	对边法兰型	45	S45C	无电解镀锌
NRBGK		0Cr18Ni9	SUS304	—

圆法兰型

对边法兰型



型号		Dg6	最小单位1		M	V	H	T	M1	d1	d2	h	P.C.D			
代码	规格		Y	F												
圆法兰型 NRBFH NRBFJ NRBFK	6	6	-0.004 -0.012	5~160	3	8	26	10	M4	6.5	3.5	3.5	17			
	6A						32						23			
	8	8	-0.005 -0.014		4	10	28						19			
	8A					36	26									
	10	10		12~65	4 5 6	13	32		M5	8	4.3	4.4	23			
	10A					40	30									
	12	12	-0.006 -0.017		5 6 8	15	36						26			
	13	13				16	38						27			
	15	15		18		40	30									
	16	16		19		42	31									
	17	17	-0.007 -0.020	10~160	6 8 10	20	44	32								
	18	18				21	46	34								
	20	20				24	48	36								
	22	22				26	50	15	M6	9.5	5.2	5.4	39			
	25	25	29	54	42											
	30	30	34	62	M8	11	6.8						6.5	49		
	35	35	39	70										55		
	40	40	-0.009 -0.025	20~80				12 16 20	44	80	M10	14		8.6	9	63
	50	50						16 20	54	90						73

型号		Dg6		最小单位1		M		V	H	T	M1	d1	d2	h	W	A
代码	规格			Y	F											
对边 法兰型 NRBGH NRBGJ NRBGK	6	6	-0.004 -0.012	12~65	5~160	3	8	26	10	10	M4	6.5	3.5	3.5	13	17
	8	8	-0.005 -0.014												14	19
	10	10	-0.006 -0.017												15	23
	12	12	-0.007 -0.020												19	26
	13	13	-0.008 -0.017	10~160	4 5 6	13	32	40	10	M5	8	4.3	4.4	21	27	
	15	15	-0.009 -0.025											23	30	
	16	16	-0.009 -0.025											24	31	
	17	17	-0.009 -0.025											27	32	
	18	18	-0.007 -0.020	17~80	6 8 10 12	21	46	24	48	15	M6	9.5	5.2	5.4	30	34
	20	20	-0.007 -0.020												31	36
	22	22	-0.007 -0.020												33	39
	25	25	-0.009 -0.025												37	42
	30	30	-0.009 -0.025	20~80	8 10 12 16 20	34	62	39	70	15	M8	11	6.8	6.5	41	49
	35	35	-0.009 -0.025												49	55
	40	40	-0.009 -0.025												55	63
	50	50	-0.009 -0.025												69	73

可选加工

代码	技术说明	
YC	变更Y尺寸公差	选型方法 YC ① 变更Y尺寸公差为±0.04
		
AD	增加引导部	选型方法 AD ① 在如左图所示位置增加引导部
	